



DOO ZA SPOLJNI I UNUTRAŠNJI PROMET

Rumenački put 39, 21201 Rumenka, Srbija

Tel/fax: +381 (021)540-438, 540-426, 543-115

e-mail: office@vgp.rs

www.vgp.rs

Mini utovarivač----ZJ60



SPECIFIKACIJA	Podizna moć (kg)	850
	Opterećenje pri kačenju(kg)	1700
	Kapacitet kašike(m3)	0.4-0.5
	Radna težina(kg)	3200
	Max. brzina kretanja(km/h)	12
	Danfoss hidraulična pumpa(L/min)	75
	Kapacitet rezervoara za gorivo(L)	80
	Gume	12-16.5
	Dužina – širina - visina(mm)	3840×1820×2080
Dimenzije	Visina na maksimalnom produžetku (mm)	3690
	Visina do zglobove osovine kašike (mm)	2920
	Širina sa kašikom (mm)	1820
	Širina gaza(mm)	1500
	Međuosovinsko rastojanje (mm)	991
	Razmak od tla - klirens(mm)	205
	Ugao istovara	40°
	Visina izbacivanja (mm)	2330

Motor	Model LOVOL	60 KS / 2650 rpm
	Tip	4 cilindra u liniji, vodeno hlađenje, četvorotaktni, dizel motor
	Type	2.54
Standardna oprema		Sistem upravljanja rukom (mehanički tip)
		Standardna kašika 180 cm
		Pomoćne hidraulične spojnice (uobičajene kao Bobcat)
		Kabina rukovaoca otvorenog tipa
Opcije		Hidraulične komande džojstika
		Zatvorena kabina rukovaoca sa klima uređajem
		Kabina opremljena grejačem
Prilozi		Rovokopač, razbijač, ugaona sečiva, svrdlo, stroj za čišćenje, viljuška za palete, kombinaciona kašika, kosačica, sekač asfalta, mešalica za beton I drugo



