## FORESTRY MULCHERS FOR EXCAVATORS

# PML/HY

# FAE forestry mulcher for mini-excavators.

The PML/HY is FAE's smallest forestry mulcher head for excavators. It is perfect for clearing saplings and shredding brush up to 4 cm in diameter. The PML/HY forestry mulcher can come equipped with a standard 8 cc engine or an optional 16 cc engine, and can be mounted on 1.5-3.5 ton excavators. The rotor on the PML/HY is available with two different types of teeth: the PML hammer or the Y/2 blade. Internal counterblades, flying debris protection, a rear roller, and steel construction provide professional quality and superior performance.



**Customized attachment bracket** (optional)



Self-cleaning support roller

#### **Enclosed machine body**

#### Steel counter-blades

helps mulch material into a smaller final size



### **MAIN OPTIONS**



**Customized attachment** bracket



Attachment plate with self leveling device to adapt to all types of terrain



Possibillity to have the rotor equipped with PML





#### STANDARD EQUIPMENT

8 cc gear motor with integrated anticavitation valve (19-40 L/min)	Self levelling protection rubber
Enclosed / anti dust machine body	Supporting service leg
Motor enclosed in the frame	Welded counterblades
Belt transmission	Rear roller
Hydraulic hoses	

#### **OPTIONS**

16 cc gear motor with integrated anticavitation valve (38-60 L/min)	Attachment plate with self levelling device
Flow control system valve (only for PML/HY-70 and PML/HY-90)	Possibillity to have the rotor equipped with PML hammers or Y-flails
Customized attachment bracket with pins	

MODEL	PML/HY 50	PML/HY 70	PML/HY 90
Flow rate (L/min)	19-60	19-60	19-60
Pressure (bar)	150-210	150-210	150-210
Excavator weight (t)	1,5-3,5	2,0-3,5	2,5-3,5
Working width (mm)	500	700	900
Weight (kg)	180	195	210
Rotor diameter (mm)	360	360	360
Max shredding diameter (mm)	40	40	40
No. hammers type PML	8	10	14
No. flail type Y/2	8	10	14

 ${\it Data\ refers\ to\ machine\ as\ standard.}\ The\ technical\ data\ in\ this\ catalogue\ may\ be\ altered\ without\ prior\ notice.$ 



