


FORESTRY MULCHERS FOR EXCAVATORS


PMM/EX

Mulcher with hammer/flail rotor for excavators.

The PMM/EX is a flail mower used to mulch underbrush, grass and bushes. It is equipped with a variable manual displacement hydraulic piston motor that can be set to the carrier's hydraulic specifications. The stronger roller supports (optional)

ensure the best performance and maximum reliability on difficult terrain. The flow control valve ensures minimal setup of the mulcher without adjustments or modifications to the hydraulic system of the excavator.

 55-145 L/min

 Ø 8 cm max

 6-13 t



Steel counter-blades
helps mulch material into
a smaller final size



Self-cleaning support roller

Enclosed machine body



**Stronger bearings
for the support roller**



STANDARD EQUIPMENT

32/65 cc variable manual displacement hydraulic piston motor	Bulkhead for hydraulic connections
Flow control system valve	Rear hood with mechanical adjustment
Safety and anticavitation valve	Adjustable skids
Enclosed / anti dust machine body	Self levelling protection flaps
Motor enclosed in the frame	Welded counterblades
Belt transmission	Self cleaning rear roller with integrated skids


OPTIONS

Customized setting hydraulic motor	Attachment plate with self levelling device
Customized attachment bracket with pins	Possibility to have the rotor equipped with PML hammers or Y-flails

MODEL	PMM/EX 100	PMM/EX 125	PMM/EX 150
Flow rate (L/min)	55-145	55-145	55-145
Pressure (bar)	180-350	180-350	180-350
Excavator weight (t)	6-13	6-13	6-13
Working width (mm)	1060	1300	1540
Weight (kg)	520	600	680
Rotor diameter (mm)	440	440	440
Max shredding diameter (mm)	80	80	80
No. hammers type PMM	12	16	18
No. flails type Y/3	12	16	18

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.

MAIN OPTIONS



**Customized setting
hydraulic motor**



**Attachment plate with self
levelling device**
to adapt to all types of terrain



**Possibility to have the
rotor equipped with PML
hammers or Y-flail**



HAMMER PMM
(standard)



FLAIL Y/3
(option)