

## STUMP CUTTERS FOR EXCAVATORS

# SCM/EX/VT

### Disc stump cutters for excavators.

The SCM/EX/VT is designed to remove stumps quickly and easily. The front hood with hydraulic adjustment and front fixed thumb are designed to shift previously cut material. This feature combined with the

reliability and resistance of the disc allows for the best performance and safety while the stumps are being removed.



130-185 L/min



14-24 t



Access panel

VT motor  
to increase performance  
and reduce operating costs



Front hydraulic hood with bolt-on chains/protection plates



Motor enclosed in frame  
protected from dirt and damage

Adjustable supporting service stand  
for storing the machine when not in use

#### STANDARD EQUIPMENT

160/108cc variable torque hydraulic piston motor	Bulkhead for hydraulic connections
Flow control system valve	Hydraulic front hood
Safety and anticavitation valve	Screwed protection chains
Enclosed / anti dust machine body	Bolt-on chains / protection plates
Motor enclosed in the frame	Supporting service leg
Poly Chain® belt transmission	

#### OPTIONS

Customized setting hydraulic motor	Customized attachment bracket with pins
Diverter valve (plug & play)	Customized attachment bracket with pins and leg
Front fixed thumb bracked	

#### MODEL


	SCM/EX/VT
Flow rate (L/min)	130-185
Pressure (bar)	220-350
Excavator weight (t)	14-24
Total width (mm)	780
Weight (kg)	1100
Rotor diameter (mm)	790
No. teeth type M1+M2+M3+M4	12+3+12+3

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.

#### MAIN OPTIONS



Front fixed thumb



Customized setting hydraulic motor



Customized attachment bracket with fixed thumb



Customized attachment bracket

#### DISC ROTOR



M3  
(standard)



M1  
(standard)



M4  
(standard)



M2  
(standard)